

Package: dawaR (via r-universe)

September 20, 2024

Title An API Wrapper Package for DAWA - The Danish Address Web API

Date 2024-09-16

Version 0.1.0

Description Package providing functions to interact with all sections of the official Danish Address Web API (also known as DAWA). The development of this package is completely independent from the [government entity that maintains the API](sdf.dk).

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

URL <https://dawar.aleksanderbl.dk/>,
<https://github.com/aleksanderbl29/dawaR>

BugReports <https://github.com/aleksanderbl29/dawaR/issues>

Suggests knitr, rmarkdown, ggplot2, testthat (>= 3.0.0), cowplot (>= 1.1.0), rmapshaper (>= 0.5.0), microbenchmark (>= 1.5.0), dplyr

Config/testthat/edition 3

Config/testthat/parallel true

Depends R (>= 3.5.0)

Imports cli, httr2, sf, tidyRSS

VignetteBuilder knitr

Repository <https://aleksanderbl29.r-universe.dev>

RemoteUrl <https://github.com/aleksanderbl29/dawaR>

RemoteRef universe-release

RemoteSha 68967ad5e56c362e9be87a00be1ef7df040223f5

Contents

autocomplete	2
available_sections	3
dawa	3
get_data	4
get_map_data	5
reverse	6
status_check	6
Index	8

autocomplete	<i>Base function for interacting with autocomplete of sections.</i>
--------------	---

Description

This function is very handy when needing to either validate or simply "fill in gaps" with autocomplete from the API.

Usage

```
autocomplete(section, input, ...)
```

Arguments

section	Defines what section of the api should be called. <code>available_sections()</code> exposes all options for this parameter.
input	The input to autocomplete. Could be a name, a place and similar.
...	<dynamic-dots> input query parameters.

Value

Returns the autocomplete information for the provided `section` given the `input`.

Examples

```
autocomplete("regioner", "midt")
```

available_sections	<i>List of available sections for dawa()</i>
--------------------	--

Description

Simple function to list all available options for the section parameter in `dawa()`. Useful when getting to know the base api function of this package.

Usage

```
available_sections(as_list = FALSE, format = NULL, verbose = TRUE)
```

Arguments

<code>as_list</code>	This options controls the output format. The output is either a named list or an atomic vector with the available sections
<code>format</code>	Specify a format type. The function now returns only available sections that can respond with that format. Currently <code>geojson</code> is the only format that is specified.
<code>verbose</code>	whether or not to provide <code>{cli}</code> output for the user. Enabled by default, but disabled for all functions that wrap this function

Value

The function returns either a named list or an atomic vector with the available sections in the API. The format is decided by `as_list`.

Examples

```
available_sections()
available_sections(as_list = TRUE)
```

<code>dawa</code>	<i>Base API function</i>
-------------------	--------------------------

Description

This function is the foundation of all communication with the api in this package. Not intended for end-users, but it provides all the flexibility of the api without the nice conveniences of the other functions in this package. By default it reformats the api response (which is `json`) to a list object.

Usage

```
dawa(
  section,
  ...,
  append_to_url = NULL,
  format = NULL,
  verbose = TRUE,
  cache = TRUE,
  dry_run = FALSE
)
```

Arguments

section	Defines what section of the api should be called. <code>available_sections()</code> exposes all options for this parameter.
...	<dynamic-dots> input query parameters.
append_to_url	This options enables you to append a string to the url. It is inserted in the request after the <code>section</code> but before the ...
format	The format to provide as a query parameter for the api call. By default it has value <code>NULL</code> and triggers default json formatting. When <code>geojson</code> or <code>geojsonz</code> is provided, the function will return the raw json data instead of the usual list.
verbose	whether or not to provide <code>{cli}</code> output for the user. Enabled by default, but disabled for all functions that wrap this function
cache	Option to use caching in a <code>tempdir()</code> . Enabled by default. More info can be found in the documentation for <code>httr2::req_cache()</code> .
dry_run	With this option enabled, the function will output the request that has been created - Without sending it to the api. This is useful for debugging.

Value

By default returns the API response as a list output. For `geojson(z)` formats it returns the raw json. When `dry_run = TRUE` it returns the request that has been created but does not run it.

Examples

```
x <- dawa(section = "sogne")
x[[1]]
```

```
get_data
```

```
Get data from section
```

Description

Get data from section

Usage

```
get_data(section, as_list = FALSE)
```

Arguments

section	Defines what section of the api should be called. available_sections() exposes all options for this parameter.
as_list	Whether or not to return the data as a list or in a dataframe. Data.frame is the default output.

Value

Returns either a dataframe with all the data for the specified section or a list with the same information.

Examples

```
x <- get_data("regioner")
head(x)
```

get_map_data	<i>Fetch map data to use with {sf}.</i>
--------------	---

Description

This function returns map data from DAWA. It is ready to use with {sf} functions. The returned dataframe has date-time columns to inform when the information was last changed. It is returned in Europe/Copenhagen time as that is the *local time* for the API. You can change that behavior by setting `Sys.setenv(TZ = "Your/Timezone")`.

Usage

```
get_map_data(type)
```

Arguments

type	Defines the type of map data to request from DAWA. Run available_sections(format = "geojson") to see your options.
------	--

Value

Returns a data.frame object that contains polygons for the section provided.

Examples

```
x <- get_map_data("regioner")
ggplot2::ggplot(x) +
  ggplot2::geom_sf()
```

reverse	<i>Base function for interacting with reverse geocoding of sections.</i>
---------	--

Description

This function reverse geocodes the coordinates provided. When used out of the box, the function wants WGS84 coordinates (lat/long). ETRS89 or UTM zone 32 can be provided as well. When coordinates from outside of Denmark is provided, the function will fail with a code 404.

Usage

```
reverse(section, x, y, verbose = TRUE, type = NULL, ...)
```

Arguments

section	Defines what section of the api should be called. <code>available_sections()</code> exposes all options for this parameter.
x	The X coordinate to geocode. If no <code>srid</code> is provided this should be the latitude.
y	The Y coordinate to geocode. If no <code>srid</code> is provided this should be the longitude.
verbose	whether or not to provide <code>{cli}</code> output for the user. Enabled by default, but disabled for all functions that wrap this function
type	The coordinate type for the API to parse. By default none is provided and WGS84 is used. The options are ETRS89, UTM32 and WGS84. The functions checks the input against the available types and errs if the type is not allowed.
...	<code><dynamic-dots></code> input query parameters.

Value

Returns a list object with information about the provided section for the location that is input.

Examples

```
reverse("regioner", x = 12.58515, y = 55.68324)
```

status_check	<i>Check that all DAWA services are operational</i>
--------------	---

Description

This function fetches the status of all available SDFI services. The API that this package wraps is one of these. It checks [this status url](#). The status can also be followed on the official [X-page](#).

Usage

```
status_check(return_df = FALSE, error_if_unavailable = FALSE)
```

Arguments

`return_df` This option makes the function return a dataframe object with the services and their statuses listed

`error_if_unavailable` This option forces the function to throw an error in the event that one or more services are unreachable.

Value

Returns a data frame object with the services and their statuses. Is only returned if `return_df = TRUE`.

Examples

```
status_check()  
  
status_check(return_df = TRUE)
```

Index

autocomplete, [2](#)
available_sections, [3](#)

dawa, [3](#)

get_data, [4](#)
get_map_data, [5](#)

reverse, [6](#)

status_check, [6](#)